

Flexi Sealer 10000



Flexi Sealer

Flexi Sealer 10000

The Reliable and Flexible Sealer

Safe & Economical

- ▶ With a speed of up to 10,000 sealed documents per hour, the major plus points of the Flexi Sealer 10000 are its great flexibility and short pay-back time.
- ▶ Jam detectors all along the paper path increase reliability and reduce expensive reprints to a minimum.

Unique Technique

- ▶ The unique sealing technique utilizing both heat and pressure is extraordinarily versatile.
- ▶ It efficiently processes various kinds of **preglued forms** or **toner-framed paper** for sealing documents.

Cut Sheet & Continuous Forms

- ▶ The standard Flexi Sealer processes cut sheets.
- ▶ As an option the system can be connected directly to a burster or a cutter for processing continuous forms.

Flexibility

- ▶ The flexibility of the Flexi Sealer 10000 makes production, paper handling and maintenance very user-friendly.
- ▶ The modular concept adds to the service-friendliness of the system.
- ▶ Compact and robust – the attractive design of the Flexi Sealer 10000.

Easy to Operate

- ▶ The Flexi Sealer 10000 is easy to operate.
- ▶ No specialized training is required.
- ▶ Formats can be changed quickly and easily without the use of any tools.

Versatility & Cost-Efficiency

- ▶ The system is equipped with two folding pockets for single, wrap, Z or double folding.
- ▶ Optional perforation wheels are a cost-efficient alternative. Simply print the forms and let the Flexi Sealer fold, perforate and seal them ready for mailing.



Infeed/uprighting



Modules: Heating, Pressure, Perforation

Technical Data

Standard Equipment

- Infeed and upright unit
- 2-folding unit with snap locking
- 4 heater modules
- 4 pressure wheels
- Electronic jam controls
- Turning unit

Options

- Microprocessor controlled, PLC
- Stacker table
- Perforation wheels
- Counter
- Supporting stand
- External connection to stand-alone machines for continuous forms
- On-line connection to printer

Dimensions

Height	300 mm
Width	530 mm
Length, excl. stacker	1,710 mm
Length, incl. stacker	2,410 mm
Weight	75 kg

Finish

Two coloured

Connected Loads

Nominal current	230 V/10 Amp, ± 10 % (1 phase)
Nominal frequency	50/60 Hz
Power input	max. 1.4 kW
Heat emission	approx. 0.84 kJ/s

Output

4 speed

up to 10,000 sheets/hour

Paper Specifications

Length	8" - 14"
Width	200 - 220 mm
Weight	90 - 120 gr/m ²
Thickness	0.90 - 0.12 mm

Fold Types

Single fold, symmetrical
Z-fold
Wrap fold

Other formats and weights on request.



BÖWE SYSTEC AB
Rissneleden 140-142
Box 2016
17402 Sundbyberg, Sweden
Phone: + 46 8 564 212 20
Fax: + 46 8 564 212 21