

UNISTACKER / BOXIT



Uni-Stacker is a receiving system that, thanks to its vertically installed input device and choice receiving packet which can change for driving from left, right or straight forwards can be adjusted to most of the inserting systems.

With vertical stacking the Uni-Stacker handles up to 1500 envelopes (with extension model up to 3000 depending on thickness).

Emptying of the platform can therefore happen with longer time intervals which frees time for operator to perform other activities.

The programme button quickly changes to normal stacking "scaling" as needed.

Uni-Stacker together with Boxit is a unique system which with a simple method ensures that the operator does not need to lift envelopes from the receiving table.

The operator need only to draw out a package of envelopes and press a pedal for the envelopes fall into a postbox which then moves sideways while a new box automatically feeds down and waiting for new envelopes.

Boxit is constructed to easily change between postboxes of different formats.

Technical Data Uni-stacker

Height	1050 mm
Width	370 mm
Length	1800 mm
Weight	75 kg
Voltage	220-240 V
Power input	max 0,14 kW
Heat emission	ca. 0,084 kJ/s
Finish	two-coloured

Options

Extension module	(1100 mm)
Electronic alarm/stop at full stacker	
Extra width for C4/B4	(500 mm)

Technical Data Boxit

Height	940 mm
Width	1250 mm
Length	1410 mm
Weight	50 kg
Postbox magazine	3 boxes in/out
Finish	two-coloured

Options

Extension module + 3 boxes in/out	
-----------------------------------	--